

Reference: 3RT2036-1AL20

CONTACTOR, AC3:22KW/400V, 1NO
+1NC, 230V AC 50/60HZ, 3-POLE, SIZE
S2, SCREW TERMINAL

Buy it at [Electric Automation Network](#)



product brand name	SIRIUS
Product designation	3RT2 contactor
General technical data:	
Size of contactor	S2
Product extension	
function module for communication	No
Auxiliary switch	Yes
Insulation voltage	
rated value	690 V
Degree of pollution	3
Surge voltage resistance rated value	6 kV
maximum permissible voltage for safe isolation	
between coil and main contacts acc. to EN 60947-1	400 V
Protection class IP	
on the front	IP20
of the terminal	IP00
Shock resistance	
at rectangular impulse	
— at AC	11.8g / 5 ms, 7.4g / 10 ms
with sine pulse	
— at AC	18.5g / 5 ms, 11.6g / 10 ms

Mechanical service life (switching cycles)	
of contactor typical	10 000 000
of the contactor with atd>	5 000 000
of the contactor with atd>	10 000 000
Ambient conditions:	
Installation altitude at height above sea level maximum	2 000 m
Ambient temperature	
during operation	-25 ... +60 °C
during storage	-55 ... +80 °C
Main circuit:	
Number of NO contacts for main contacts	3
Number of NC contacts for main contacts	0
Operating voltage	
at AC-3 rated value maximum	690 V
Operating current	
at AC-1 at 400 V	
— at ambient temperature 40 °C rated value	70 A
at AC-1	
— up to 690 V at ambient temperature 40 °C rated value	70 A
— up to 690 V at ambient temperature 60 °C rated value	60 A
at AC-2 at 400 V rated value	51 A
at AC-3	
— at 400 V rated value	51 A
— at 500 V rated value	50 A
— at 690 V rated value	24 A
Connectable conductor cross-section in main circuit at AC-1	
at 60 °C minimum permissible	16 mm ²
at 40 °C minimum permissible	25 mm ²
Operating current for approx. 200000 operating cycles at AC-4	
at 400 V rated value	24 A
at 690 V rated value	20 A
Operating current	
at 1 current path at DC-1	
— at 24 V rated value	55 A
— at 110 V rated value	4.5 A
— at 220 V rated value	1 A

— at 440 V rated value	0.4 A
— at 600 V rated value	0.25 A
with 2 current paths in series at DC-1	
— at 24 V rated value	55 A
— at 110 V rated value	45 A
— at 220 V rated value	5 A
— at 440 V rated value	1 A
— at 600 V rated value	0.8 A
with 3 current paths in series at DC-1	
— at 24 V rated value	55 A
— at 110 V rated value	55 A
— at 220 V rated value	45 A
— at 440 V rated value	2.9 A
— at 600 V rated value	1.4 A
Operating current	
at 1 current path at DC-3 at DC-5	
— at 24 V rated value	35 A
— at 110 V rated value	2.5 A
— at 220 V rated value	1 A
— at 440 V rated value	0.1 A
— at 600 V rated value	0.06 A
with 2 current paths in series at DC-3 at DC-5	
— at 110 V rated value	25 A
— at 220 V rated value	5 A
— at 24 V rated value	55 A
— at 440 V rated value	0.27 A
— at 600 V rated value	0.16 A
with 3 current paths in series at DC-3 at DC-5	
— at 110 V rated value	55 A
— at 220 V rated value	25 A
— at 24 V rated value	55 A
— at 440 V rated value	0.6 A
— at 600 V rated value	0.35 A
Operating power	
at AC-1	
— at 230 V rated value	26 kW
— at 230 V at 60 °C rated value	23 kW
— at 400 V rated value	46 kW

— at 400 V at 60 °C rated value	39 kW
— at 690 V rated value	79 kW
— at 690 V at 60 °C rated value	68 kW
at AC-2 at 400 V rated value	22 kW
at AC-3	
— at 230 V rated value	15 kW
— at 400 V rated value	22 kW
— at 500 V rated value	30 kW
— at 690 V rated value	22 kW
Operating power for approx. 200000 operating cycles at AC-4	
at 400 V rated value	12.6 kW
at 690 V rated value	18.2 kW
Thermal short-time current limited to 10 s	420 A
Power loss [W] at AC-3 at 400 V for rated value of the operating current per conductor	4 W
No-load switching frequency	
at AC	5 000 1/h
Operating frequency	
at AC-1 maximum	1 000 1/h
at AC-2 maximum	600 1/h
at AC-3 maximum	800 1/h
at AC-4 maximum	250 1/h
Control circuit/ Control:	
Type of voltage of the control supply voltage	AC
Control supply voltage at AC	
at 50 Hz rated value	230 V
at 60 Hz rated value	230 V
Operating range factor control supply voltage rated value of magnet coil at AC	
at 50 Hz	0.8 ... 1.1
at 60 Hz	0.85 ... 1.1
Apparent pick-up power of magnet coil at AC	
at 50 Hz	210 V·A
at 60 Hz	188 V·A
Apparent holding power of magnet coil at AC	
at 50 Hz	17.2 V·A
at 60 Hz	16.5 V·A
Closing delay	

at AC	10 ... 80 ms
Opening delay	
at AC	10 ... 18 ms
Arcing time	10 ... 20 ms
Auxiliary circuit:	
Number of NC contacts	
for auxiliary contacts	
— instantaneous contact	1
Number of NO contacts	
for auxiliary contacts	
— instantaneous contact	1
Operating current at AC-12 maximum	10 A
Operating current at AC-15	
at 230 V rated value	10 A
at 400 V rated value	3 A
at 500 V rated value	2 A
at 690 V rated value	1 A
Operating current at DC-12	
at 24 V rated value	10 A
at 48 V rated value	6 A
at 60 V rated value	6 A
at 110 V rated value	3 A
at 125 V rated value	2 A
at 220 V rated value	1 A
at 600 V rated value	0.15 A
Operating current at DC-13	
at 24 V rated value	10 A
at 48 V rated value	2 A
at 60 V rated value	2 A
at 110 V rated value	1 A
at 125 V rated value	0.9 A
at 220 V rated value	0.3 A
at 600 V rated value	0.1 A
Contact reliability of auxiliary contacts	1 faulty switching per 100 million (17 V, 1 mA)
UL/CSA ratings:	
Full-load current (FLA) for three-phase AC motor	
at 480 V rated value	52 A
at 600 V rated value	52 A

Yielded mechanical performance [hp]	
for single-phase AC motor	
— at 110/120 V rated value	3 hp
— at 230 V rated value	10 hp
for three-phase AC motor	
— at 200/208 V rated value	15 hp
— at 220/230 V rated value	15 hp
— at 460/480 V rated value	40 hp
— at 575/600 V rated value	50 hp
Contact rating of auxiliary contacts according to UL	A600 / P600
Short-circuit protection	
Design of the fuse link	
for short-circuit protection of the main circuit	
— with type of coordination 1 required	gL/gG NH 3NA, DIAZED 5SB, NEOZED 5SE: 160 A
— with type of assignment 2 required	gL/gG NH 3NA, DIAZED 5SB, NEOZED 5SE: 80 A
for short-circuit protection of the auxiliary switch required	fuse gL/gG: 10 A
Installation/ mounting/ dimensions:	
Mounting position	+/-180° rotation possible on vertical mounting surface; can be tilted forward and backward by +/- 22.5° on vertical mounting surface
Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail according to DIN EN 50022
Side-by-side mounting	Yes
Height	114 mm
Witd>	55 mm
Depth	130 mm
Required spacing	
with side-by-side mounting	
— forwards	0 mm
— Backwards	0 mm
— upwards	0 mm
— downwards	0 mm
— at the side	0 mm
for grounded parts	
— forwards	10 mm
— Backwards	0 mm
— upwards	50 mm
— at the side	6 mm
— downwards	50 mm

for live parts	
— forwards	10 mm
— Backwards	0 mm
— upwards	50 mm
— downwards	50 mm
— at the side	6 mm
Connections/Terminals:	
Type of electrical connection	
for main current circuit	screw-type terminals
for auxiliary and control current circuit	screw-type terminals
Type of connectable conductor cross-sections	
for main contacts	
— single or multi-stranded	2x (1 ... 35 mm ²), 1x (1 ... 50 mm ²)
— finely stranded with core end processing	2x (1 ... 25 mm ²), 1x (1 ... 35 mm ²)
at AWG conductors for main contacts	2x (18 ... 2), 1x (18 ... 1)
Type of connectable conductor cross-sections	
for auxiliary contacts	
— single or multi-stranded	2x (0,5 ... 1,5 mm ²), 2x (0,75 ... 2,5 mm ²)
— finely stranded with core end processing	2x (0.5 ... 1.5 mm ²), 2x (0.75 ... 2.5 mm ²)
at AWG conductors for auxiliary contacts	2x (20 ... 16), 2x (18 ... 14)
Safety related data:	
B10 value	
with high demand rate acc. to SN 31920	1 000 000
Proportion of dangerous failures	
with low demand rate acc. to SN 31920	40 %
with high demand rate acc. to SN 31920	73 %
Product function	
Mirror contact acc. to IEC 60947-4-1	Yes
positively driven operation acc. to IEC 60947-5-1	No
T1 value for proof test interval or service life acc. to IEC 61508	20 y