



EA Electric Automation

Automation specialists

Reference: 6SL3210-5BB21-5AV0

SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 1,5KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C2 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSB 140X160X165(WXHXD)

Buy it at Electric Automation Network



Product	
Article Number (Market Facing Number)	6SL3210-5BB21-5AV0
Product Description	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 1,5KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C2 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSB 140X160X165(WXHXD)
Product family	SINAMICS V20 basic converters
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group / Headquarter Price Group	325 / 350
List Price	Show prices
Customer Price	Show prices
Metal Factor	None
Delivery information	
Export Control Regulations	AL : N / ECCN : N
Standard lead time ex-works	3 Day/Days
Net Weight (kg)	1,800 Kg
Product Dimensions (W x L x H)	Not available
Packaging Dimension	203,00 x 200,00 x 190,00
Package size unit of measure	ММ
Quantity Unit	1 Piece

Packaging Quantity	1			
Atd>				
EAN	6940408103016			
UPC	887621204013			
Commodity Code	85044084			
LKZ_FDB/ CatalogID	SINAMICS V20			
Product Group	5680			
Country of origin	China			
Compliance with the substance restrictions according to RoHS directive	Since: 05/07/10			
Product class	C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.			
Obligation Category for taking back electrical and electronic equipment after use	No obligation to take back electrical and electronic equipment after use			
Classifications				
		Version	Classification	
	eClass	5.1	27-02-31-01	
	eClass	6	27-02-31-01	
	eClass	7.1	27-02-31-01	
	eClass	8	27-02-31-01	
	eClass	9	27-02-31-01	
	eClass	9.1	27-02-31-01	
	ETIM	4	EC001857	
	ETIM	5	EC001857	
	ETIM	6	EC001857	
	UNSPSC	14	39-12-10-07	
	UNSPSC	15	39-12-10-07	