SIEMENS



Reference: 6SL3210-5BB23-0AV0

SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 3,0KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C2 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSC 184X182X169(WXHXD)

Buy it at Electric Automation Network



Product			
Article Number (Market Facing Number)	6SL3210-5BB23-0AV0		
Product Description	SINAMICS V20 1AC200-240V -10/+10% 47-63HZ RATED POWER 3,0KW WITH 150% OVERLOAD FOR 60SEC INTEGRATED FILTER C2 I/O-INTERFACE: 4DI, 2DO,2AI,1AO FIELDBUS: USS/ MODBUS RTU WITH INBUILT BOP PROTECTION: IP20/ UL OPEN TYPE SIZE:FSC 184X182X169(WXHXD)		
Product family	SINAMICS V20 basic converters		
Product Lifecycle (PLM)	PM300:Active Product		
Price data			
Price Group / Headquarter Price Group	325 / 350		
List Price	Show prices		
Customer Price	Show prices		
Metal Factor	None		
Delivery information			
Export Control Regulations	AL: N / ECCN: N		
Standard lead time ex-works	3 Day/Days		
Net Weight (kg)	2,800 Kg		
Product Dimensions (W x L x H)	Not available		
Packaging Dimension	237,00 x 220,00 x 247,00		
Package size unit of measure	ММ		
Quantity Unit	1 Piece		

Packaging Quantity	1		
Atd>			
EAN	6940408103030		
UPC	887621204037		
Commodity Code	85044084		
LKZ_FDB/ CatalogID	SINAMICS V20		
Product Group	5680		
Country of origin	China		
Compliance with the substance restrictions according to RoHS directive	Since: 05/07/10		
Product class	C: products manufactured / produced to order, which cannot be reused or re-utilised or be returned against credit.		
Obligation Category for taking back electrical and electronic equipment after use	No obligation to take back electrical and electronic equipment after use		
Classifications			
		Version	Classification
	eClass	5.1	27-02-31-01
	eClass	6	27-02-31-01
	eClass	7.1	27-02-31-01
	eClass	8	27-02-31-01
	eClass	9	27-02-31-01
	eClass	9.1	27-02-31-01
	ETIM	4	EC001857
	ETIM	5	EC001857
	ETIM	6	EC001857
	UNSPSC	14	39-12-10-07
	UNSPSC	15	39-12-10-07