

Reference: 3SB3801-0AD3

ENCLOSURE FOR 22MM PROGRAM
PLASTIC VERSION 1 COMMAND
POSITION YELLOW TOP PART WITH
PROTECTIVE COLLAR FOR EMERGEN.-
STOP

[Buy it at Electric Automation Network](#)



| | |
|---|---|
| Enclosure: | |
| Design of the housing | Empty enclosure for command and signaling devices |
| Shape of the enclosure front | Square |
| Material of the enclosure | plastic |
| Number of command points | 1 |
| Product component | |
| protective collar | Yes |
| Color | |
| of top part of the enclosure | yellow |
| Delivery state | |
| as a kit | No |
| pre-wired on strip terminal | No |
| Mounting type of the enclosure | Vertical / horizontal |
| Actuator: | |
| Product feature | |
| lockout | No |
| Product extension optional Light source | Yes |
| Front ring: | |
| Product component front ring | No |
| General technical data: | |
| Product function | |

| | |
|---|--|
| positive opening | No |
| EMERGENCY STOP function | No |
| Product component | |
| Light source | No |
| Stand/pedestal | No |
| Protection class IP | IP65 |
| Vibration resistance | |
| acc. to IEC 60068-2-6 | 20 ... 200 Hz: 5g |
| Equipment marking | |
| acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 | S |
| acc. to DIN EN 61346-2 | U |
| acc. to DIN EN 81346-2 | U |
| Connections/ Terminals: | |
| Type of electrical connection on enclosure | Cable routing above, below / left, right, each 1 x M20 |
| Ambient conditions: | |
| Ambient temperature | |
| during operation | -25 ... +70 °C |
| during storage | -40 ... +80 °C |
| Environmental category during operation acc. to IEC 60721 | 3K6 |
| Installation/ mounting/ dimensions: | |
| Mounting type | |
| of contact blocks, socket, and accessories | Floor mounting / front mounting (1-pole) |
| Height | 85 mm |
| Witd> | 85 mm |
| Depth | 106 mm |
| Shape of the installation opening | round |
| Mounting diameter | 22 mm |
| Accessories: | |
| Number of labels | 0 |
| Product component holder for 3 switching elements | No |