

Reference: 3SB3802-0AA3

ENCLOSURE FOR 22MM PROGRAM
PLASTIC VERSION 2 COMMAND
POSITIONS GRAY TOP PART

Buy it at [Electric Automation Network](#)



Enclosure:	
Design of the housing	Empty enclosure for command and signaling devices
Shape of the enclosure front	rectangular
Material of the enclosure	plastic
Number of command points	2
Product component	
protective collar	No
Color	
of top part of the enclosure	grey
Delivery state	
as a kit	No
pre-wired on strip terminal	No
Mounting type of the enclosure	Vertical / horizontal
Actuator:	
Product feature	
lockout	No
Product extension optional Light source	Yes
Front ring:	
Product component front ring	No
General technical data:	
Product function	

positive opening	No
EMERGENCY STOP function	No
Product component	
Light source	No
Stand/pedestal	No
Protection class IP	IP65
Vibration resistance	
acc. to IEC 60068-2-6	20 ... 200 Hz: 5g
Equipment marking	
acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	S
acc. to DIN EN 61346-2	U
acc. to DIN EN 81346-2	U
Connections/ Terminals:	
Type of electrical connection on enclosure	Cable routing above, below / left, right, each 1 x M20
Ambient conditions:	
Ambient temperature	
during operation	-25 ... +70 °C
during storage	-40 ... +80 °C
Environmental category during operation acc. to IEC 60721	3K6
Installation/ mounting/ dimensions:	
Mounting type	
of contact blocks, socket, and accessories	Floor mounting / front mounting (1-pole)
Height	114 mm
Witd>	85 mm
Depth	64 mm
Shape of the installation opening	round
Mounting diameter	22 mm
Accessories:	
Number of labels	2
Product component holder for 3 switching elements	No