

Reference: 3VA2463-5HL32-0AA0

CIRCUIT BREAKER 3VA2 IEC FRAME 630  
BREAKING CAPACITY CLASS M ICU=55KA  
@ 415 V 3-POLE, LINE PROTECTION  
ETU320, LI, IN=630A OVERLOAD  
PROTECTION IR=250A ...630A SHORT  
CIRCUIT PROTECTION Ii=1,5...9x In  
BUSBAR CONNECTION

Buy it at [Electric Automation Network](#)



Product	
Article Number (Market Facing Number)	3VA2463-5HL32-0AA0
Product Description	CIRCUIT BREAKER 3VA2 IEC FRAME 630 BREAKING CAPACITY CLASS M ICU=55KA @ 415 V 3-POLE, LINE PROTECTION ETU320, LI, IN=630A OVERLOAD PROTECTION IR=250A ...630A SHORT CIRCUIT PROTECTION Ii=1,5...9x In BUSBAR CONNECTION
Product family	3VA Molded Case Circuit Breakers up to 1000 A, IEC
Product Lifecycle (PLM)	PM300:Active Product
Price data	
Price Group / Headquarter Price Group	339 / 1CB
List Price	Show prices
Customer Price	Show prices
Metal Factor	LAO-----
Delivery information	
Export Control Regulations	AL : N / ECCN : EAR99
Standard lead time ex-works	2 Day/Days
Net Weight (kg)	5,176 Kg
Product Dimensions (W x L x H)	Not available
Packaging Dimension	162,00 x 261,00 x 167,00
Package size unit of measure	MM
Quantity Unit	1 Piece

Packaging Quantity	1																														
Atd>																															
EAN	4042948834121																														
UPC	Not available																														
Commodity Code	85362090																														
LKZ_FDB/ CatalogID	LV10.1																														
Product Group	5374																														
Country of origin	Czech Republic																														
Compliance with the substance restrictions according to RoHS directive	Since: 01/04/14																														
Product class	B: return restricted, please contact your Siemens partner/contact																														
Obligation Category for taking back electrical and electronic equipment after use	No obligation to take back electrical and electronic equipment after use																														
Classifications																															
	<table border="1"> <thead> <tr> <th></th> <th>Version</th> <th>Classification</th> </tr> </thead> <tbody> <tr> <td>eClass</td> <td>5.1</td> <td>27-37-04-09</td> </tr> <tr> <td>eClass</td> <td>6</td> <td>27-37-04-09</td> </tr> <tr> <td>eClass</td> <td>7.1</td> <td>27-37-04-09</td> </tr> <tr> <td>eClass</td> <td>8</td> <td>27-37-04-09</td> </tr> <tr> <td>eClass</td> <td>9</td> <td>27-37-04-09</td> </tr> <tr> <td>eClass</td> <td>9.1</td> <td>27-37-04-09</td> </tr> <tr> <td>ETIM</td> <td>4</td> <td>EC000228</td> </tr> <tr> <td>ETIM</td> <td>5</td> <td>EC000228</td> </tr> <tr> <td>ETIM</td> <td>6</td> <td>EC000228</td> </tr> </tbody> </table>		Version	Classification	eClass	5.1	27-37-04-09	eClass	6	27-37-04-09	eClass	7.1	27-37-04-09	eClass	8	27-37-04-09	eClass	9	27-37-04-09	eClass	9.1	27-37-04-09	ETIM	4	EC000228	ETIM	5	EC000228	ETIM	6	EC000228
	Version	Classification																													
eClass	5.1	27-37-04-09																													
eClass	6	27-37-04-09																													
eClass	7.1	27-37-04-09																													
eClass	8	27-37-04-09																													
eClass	9	27-37-04-09																													
eClass	9.1	27-37-04-09																													
ETIM	4	EC000228																													
ETIM	5	EC000228																													
ETIM	6	EC000228																													