

Reference: 3SB3252-6BA60

22MM PLASTIC ROUND COMPLETE UNIT
COMBINATION: INDICATOR LIGHT WITH
CONCENTRIC RINGS ILLUMINATED WITH
INTEGRATED LED 230V AC SCREW
TERMINAL WITH HOLDER WHITE

[Buy it at Electric Automation Network](#)



| | |
|---|---------------------|
| Design of the product | Complete unit round |
| Enclosure: | |
| Shape of the enclosure front | round |
| Material of the enclosure | plastic |
| Number of command points | 0 |
| Actuator: | |
| Design of the operating mechanism | indicator light |
| Product extension optional Light source | Yes |
| Color | |
| of the actuating element | White |
| Material of the actuating element | plastic |
| Shape of the actuating element | Concentric rings |
| Number of switching positions | 0 |
| Front ring: | |
| Product component front ring | No |
| Holder: | |
| Material of the holder | Plastic |
| Contact block/ lampholder: | |
| Mounting type | integrated LED |
| Number of lampholders | 1 |
| Number of switching elements | 0 |

| General technical data: | |
|---|----------------------|
| Product function | |
| positive opening | No |
| EMERGENCY STOP function | No |
| Product component | |
| Light source | Yes |
| Protection class IP | IP66 |
| Vibration resistance | |
| acc. to IEC 60068-2-6 | 20 ... 200 Hz: 5g |
| Equipment marking | |
| acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750 | H |
| acc. to DIN EN 61346-2 | P |
| acc. to DIN EN 81346-2 | P |
| Supply voltage: | |
| Type of voltage of the supply voltage | |
| of the light source | AC |
| Supply voltage 1 of the light source at AC | |
| at 50 Hz rated value | 230 V |
| at 60 Hz rated value | 230 V |
| Relative negative tolerance of the supply voltage | -15 % |
| Relative positive tolerance of the supply voltage | 10 % |
| Auxiliary circuit: | |
| Number of NC contacts | |
| for auxiliary contacts | 0 |
| Number of NO contacts | |
| for auxiliary contacts | 0 |
| Number of CO contacts | |
| for auxiliary contacts | 0 |
| Consumed current for rated value of supply voltage maximum | 17 mA |
| Connections/ Terminals: | |
| Type of electrical connection | screw-type terminals |
| Tightening torque of the screws in the bracket | 1 ... 1.2 N·m |
| Ambient conditions: | |
| Ambient temperature | |
| during operation | -25 ... +70 °C |
| during storage | -40 ... +80 °C |

| | |
|---|----------------|
| Environmental category during operation acc. to IEC 60721 | 3K6 |
| Installation/ mounting/ dimensions: | |
| Mounting type | front mounting |
| Shape of the installation opening | round |
| Mounting diameter | 22 mm |
| Mounting height | 11 mm |
| Installation width | 28 mm |
| Installation depth | 49 mm |
| Accessories: | |
| Product component holder for 3 switching elements | No |