

Product data sheet

Specifications



TeSys Deca thermal overload relays , 95...120A , class 10A

LRD4367

Product availability: Stock - Normally stocked in distribution facility

Main

| | |
|-------------------------------------|---|
| Range | TeSys |
| product name | TeSys LRD TeSys Deca |
| Product or Component Type | Differential thermal overload relay |
| Device short name | LRD |
| Relay application | Motor protection |
| Product Compatibility | LC1D150 LC1D115 |
| Network type | CA CC |
| Thermal overload class | Class 10A IEC 60947-4-1 |
| Thermal protection adjustment range | 95...120 A |
| [Ui] rated insulation voltage | Power circuit 1000 V IEC 60947-4-1 Power circuit 600 V CSA Power circuit 600 V UL |

Complementary

| | |
|---|--|
| Network Frequency | 0...400 Hz |
| Mounting support | Plate, with specific accessories Rail, with specific accessories Under contactor |
| Tripping threshold | 1.14 +/- 0.06 Ir IEC 60947-4-1 |
| Auxiliary contact composition | 1 NO + 1 NC |
| [Ith] conventional free air thermal current | 5 A signalling circuit |
| Permissible current | 0.06 A 440 V DC-13 signalling circuit 0.12 A 600 V AC-15 signalling circuit |
| [Ue] rated operational voltage | 1000 V AC 0...400 Hz power circuit IEC 60947-4-1 |
| Associated fuse rating | 4 A gG for signalling circuit 4 A BS for signalling circuit |
| [Uimp] rated impulse withstand voltage | 6 kV IEC 60947-1 |
| Phase failure sensitivity | Tripping current 130 % of Ir on two phase, the last one at 0 |
| Control type | Red push-button stop Blue push-button reset |
| Temperature compensation | -4...140 °F (-20...60 °C) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|--------------------------------|--|
| Connections - terminals | Power circuit screw clamp terminals 1 0.006...0.05 in ² (4...35 mm ²) flexible with cable end Control circuit screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²) flexible without cable end Control circuit screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²) flexible with cable end Control circuit screw clamp terminals 2 0.002...0.004 in ² (1...2.5 mm ²) solid without cable end Power circuit screw clamp terminals 1 0.006...0.08 in ² (4...50 mm ²) flexible without cable end Power circuit screw clamp terminals 1 0.006...0.08 in ² (4...50 mm ²) solid without cable end |
| Tightening torque | Control circuit 15.05 lbf.in (1.7 N.m) screw clamp terminals Power circuit 79.7 lbf.in (9 N.m) screw clamp terminals |
| Depth | 5.2 in (132 mm) |
| Net Weight | 2.0 lb(US) (0.9 kg) |

Environment

| | |
|--|--|
| Climatic withstand | IACS E10 |
| IP degree of protection | IP20 conforming to IEC 60529 |
| Ambient air temperature for operation | -4...140 °F (-20...60 °C) without derating IEC 60947-4-1 |
| Ambient Air Temperature for Storage | -76...158 °F (-60...70 °C) |
| Flame retardance | V1 conforming to UL 94 |
| Mechanical robustness | Vibrations6 Gn IEC 60068-2-6 Shocks15 Gn for 11 ms IEC 60068-2-7 |
| Dielectric strength | 2.2 kV 50 Hz IEC 60947-1 |
| Standards | EN/IEC 60947-4-1 EN/IEC 60947-5-1 UL 60947-4-1 UL 60947-5-1 CSA C22.2 No 60947-4-1 CSA C22.2 No 60947-5-1 GB/T 14048.4 GB/T 14048.5 EN 50495 |
| Product Certifications | IEC UL CSA CCC EAC ATEX INERIS |

Ordering and shipping details

| | |
|--------------------------|---------------|
| Category | US10I1222347 |
| Discount Schedule | 0112 |
| GTIN | 3389110523348 |
| Returnability | Yes |
| Country of origin | FR |

Packing Units

| | |
|-------------------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 6.10 in (15.500 cm) |
| Package 1 Width | 5.31 in (13.500 cm) |

| | |
|-------------------------------------|----------------------------|
| Package 1 Length | 4.33 in (11.000 cm) |
| Package 1 Weight | 29.277 oz (830.000 g) |
| Unit Type of Package 2 | S03 |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 11.81 in (30.000 cm) |
| Package 2 Width | 11.81 in (30.000 cm) |
| Package 2 Length | 15.75 in (40.000 cm) |
| Package 2 Weight | 19.577 lb(US) (8.880 kg) |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 80 |
| Package 3 Height | 29.53 in (75.000 cm) |
| Package 3 Width | 23.62 in (60.000 cm) |
| Package 3 Length | 31.50 in (80.000 cm) |
| Package 3 Weight | 179.289 lb(US) (81.324 kg) |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

Carbon footprint (kg CO2 eq, Total Life cycle) **8**

Environmental Disclosure [Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard **Yes**

Packaging without single use plastic **Yes**

[EU RoHS Directive](#) **Compliant**

REACH Regulation [REACH Declaration](#)

California proposition 65 **WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Circularity Profile [End of Life Information](#)

Take-back **No**