

PRODUCT-DETAILS

# ACS150-01E-02A4-2

## ACS150-01E-02A4-2 Pn 0,37kW, I2n 2,4A IP20



### General Information

Global Commercial Alias	ACS150-01E-02A4-2
Product ID	68581940
ABB Type Designation	ACS150-01E-02A4-2
EAN	6410038079307
Catalog Description	ACS150-01E-02A4-2 Pn 0,37kW, I2n 2,4A IP20
Long Description	The ACS150 drives are designed to be incorporated into a wide variety of machines such as mixers, conveyors, fans or pumps. The ACS150 drives have an integrated user panel, potentiometer and a variety of features such as pre-defined connection macros, making drive selection and configuration easy. With an optional FlashDrop tool these drives can be configured quickly in volume.

### Ordering

Country of Origin	China (CN)
Customs Tariff Number	85044084
Invoice Description	ACS150-01E-02A4-2 Pn 0,37kW, I2n 2,4A IP20
Made To Order	No
Minimum Order Quantity	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

### Dimensions

Product Net Weight	1.2 kg
Product Net Depth / Length	142 mm
Product Net Height	239 mm
Product Net Width	70 mm
Package Level 1 Depth / Length	343 mm
Package Level 1 Height	130 mm
Package Level 1 Width	217 mm
Package Level 1 Units	1 carton

## Technical

Number of Phases	1
Degree of Protection	IP20
Enclosure Type NEMA	Open Type
Frequency (f)	50/60 Hz
Input Voltage ( $U_{in}$ )	200 ... 240 V
Mounting Type	Module for cabinet building
Number of Hardware Interfaces	Industrial Ethernet 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 0 Serial TTY 0 USB 0 Parallel 0 Other 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	1
Analog Outputs	0
Number of Digital In/Outputs	5/0
Output Current, Light-Overload Use ( $I_{LD}$ )	2.4 A
Output Current, Normal Use ( $I_n$ )	2.4 A
Output Power, Light-Overload Use ( $P_{LD}$ )	0.4 kW
Output Power, Normal Use ( $P_n$ )	0.37 kW
Apparent Power Output	1.0 kV-A
Efficiency Level	IE2
Standby Loss	6 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
90 / 100 %	29 W	3.1 %	95.5 %
50 / 100 %	26 W	2.7 %	93.1 %
0 / 100 %	23 W	2.4 %	87.7 %
90 / 50 %	23 W	2.4 %	93.9 %
50 / 50 %	21 W	2.2 %	90.3 %
50 / 25 %	20 W	2.1 %	86.4 %
0 / 50 %	20 W	2.1 %	82.7 %
0 / 25 %	19 W	2.0 %	76.2 %

Temperature Rating	Maximum 40 °C
Ecodesign Exemption	Energy efficiency data is not provided for the 1~230 V drives. The drives with one phase input are not in the scope of the EU ecodesign requirements (Regulation EU/2019/1781).

### Additional Information

Product Main Type	ACS150
Product Name	Frequency converter

### Classifications

Product Series	ACS150
ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

### Environmental

SCIP	48b9142c-556f-48b8-b335-7ea8496bc698 Finland (FI)
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

### Categories

Drives → Low Voltage AC Drives → Micro Drives → ACS150 - Micro Drive

