



List No. 9700

INGRESS PROTECTED

20AX 1 Gang 2 Way IP66 Switch



- Fully Rated for Fluorescent Loads
- Protected Against Limited Ingress To Dust
- Protected Against Strong Jets of Water
- IP66

Product Specification Data

Revision Date: 11/10/2024

| | |
|---|-------------------------------|
| Product Standard/s | BS EN 60669-1 |
| Terminal Capacity L&N | 3 x 2.5, 2 x 4.0, 1 x 6.0 mm² |
| Frequency | 50 Hz |
| LRV Value | 64 |
| CE Conformity | Yes |
| WEEE Symbol | Yes |
| UKCA Conformity | Yes |
| Wiring system | Other |
| Method of operation | Rocker/button |
| Assembly arrangement | Control element |
| Number of modules (module system) | 0 |
| Push button switch | Yes |
| Number of rockers | 1 |
| Mounting method | Surface mounted |
| Type of fastening | Screw mounting |
| With mounting plate | Yes |
| Material | Other |
| Material quality | Other |
| Halogen free | Yes |
| Surface protection | Other |
| Surface finishing | Matt |
| Colour | Grey |
| Illumination | No |
| Function lighting | Other |
| Type of lighting | LED exchangeable |
| Suitable for degree of protection (IP) | IP66 |
| Nominal voltage | 250 V |
| Rated current | 20 A |
| Switching current for fluorescent lamps | 20 AX |

| | |
|-----------------|----------------|
| Connection type | Screw terminal |
| Device width | 96 mm |
| Device height | 96 mm |
| Device depth | 56 mm |



Venus Electric
Address: Salah Al-Din Al Ayoubi St, Jabal Alhussein,
Amman
Phone: +962 79196 6817
Fax: 064640203
Email: info@venuselect.com
Website: www.venuselect.com