



- Smooth and slimline profile
- Clip on front plate for clean screwless aesthetic

Product Specification Data

Revision Date: 11/10/2024

Product Standard/s	BS 5733
Frequency	50 Hz
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Model	British Standard
Number of active contacts (round)	0
Number of active contacts (flat)	2
With signal lamp	No
Number of units	1
Number of modules (module system)	0
Number of socket outlets switchable	1
Number of phases	2
Imprint/indication	Other
Connection type	Screwed terminal
With hinged lid	No
Label space/information surface	Yes
Colour	White
Lockable	No
Insulated mounting	Yes
With function lighting	No
Fault current protection	No
Special power supply	No special power supply
Mounting method	Surface mounted
Type of fastening	Mounting with screw
Material	Plastic
Material quality	Other
Halogen free	Yes
Surface protection	Other

Surface finishing	Glossy
Anti-bacterial treatment	Yes
With on/off switch	Yes
Nominal current	16 A
Nominal voltage	250 V
Suitable for degree of protection (IP)	IP2X
Impact strength	IK02
Device width	86 mm
Device height	86 mm
Min. depth of built-in installation box	35 mm



Venus Electric  
Address: Salah Al-Din Al Ayoubi St, Jabal Alhussein,  
Amman  
Phone: +962 79196 6817  
Fax: 064640203  
Email: [info@venuselect.com](mailto:info@venuselect.com)  
Website: [www.venuselect.com](http://www.venuselect.com)