

- Fully Rated for Fluorescent Loads



Product Specification Data

Revision Date: 15/10/2021

Product Standard/s	BS EN 60669-1
Terminal Capacity L&N	3 x 2.5, 2 x 4.0, 1 x 6.0 mm ²
Frequency	50 Hz
LRV Value	73
CE Conformity	Yes
WEEE Symbol	Yes
UKCA Conformity	Yes
Wiring system	Two-way switch
Method of operation	Rocker/button
Assembly arrangement	Control element
Number of modules (module system)	1
Push button switch	Yes
Number of rockers	1
Mounting method	Module frame
Type of fastening	Screw mounting
With mounting plate	No
Material	Plastic
Material quality	Thermoplastic
Halogen free	Yes
Surface protection	Other
Surface finishing	Glossy
Colour	White
Illumination	No
Function lighting	Other
Type of lighting	LED exchangeable
Suitable for degree of protection (IP)	IP2X
Nominal voltage	250 V
Rated current	20 A
Switching current for fluorescent lamps	20 AX

Connection type	Screw terminal
Width of device	25 mm
Height of device	55.5 mm
Depth of device	31 mm
Built-in depth	20.5 mm
Min. depth of built-in installation box	25 mm



Venus Electric
Address: Salah Al-Din Al Ayoubi St, Jabal Alhussein,
Amman
Phone: +962 79196 6817
Fax: 064640203
Email: info@venuselect.com
Website: www.venuselect.com